

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method of generating an output audio signal by adding output components in a predetermined first frequency range to an input signal, the output components being generated by performing a predetermined calculation on first input components in a predetermined second frequency range, characterized in that a first output energy measure, over a predetermined first time interval, of the output components generated is set, based upon a first input energy measure calculated over a predetermined second time interval of second input components, in a predetermined third frequency range of the input audio signal, wherein the predetermined third frequency range is different from the predetermined second frequency range, and is selected from a predetermined number of frequency ranges, as the frequency range which is closest to the first frequency range according to a predetermined frequency range distance formula.

2. (Cancelled).

3. (Original) A method as claimed in claim 1, wherein the first output energy measure is set by further using a second input energy measure over a predetermined third time interval of third input components, in a predetermined fourth frequency range of the input audio signal.

4. (Original) A method as claimed in claim 1, wherein the predetermined calculation comprises applying a non linear function to first input components in a predetermined second frequency range of an input audio signal.

5. An apparatus for generating an output audio signal by adding output components in a predetermined first frequency range to an input audio signal, said apparatus comprising:

-----calculation means for calculating the output components
5 from first input components in a predetermined second frequency range of the input audio signal;~~characterized in that:~~

--- filtering means ~~are comprised for~~ obtaining second input components in a third frequency range of the input audio signal;

--- energy calculation means ~~are comprised for~~ obtaining a
10 first input energy measure over a second predetermined time interval of the second input components and deriving therefrom a first output energy measure; and

--- energy setting means ~~are comprised for~~ setting the energy
15 of the output components over a first predetermined time interval substantially equal to the first output energy measure.

wherein the predetermined third frequency range is different from the predetermined second frequency range, and is selected from a predetermined number of frequency ranges, as the frequency range which is closest to the first frequency range according to a
20 predetermined frequency range distance formula.

6. (Currently Amended) An audio player, comprising:

_____audio data input means for providing an input audio
signal;

_____to an apparatus for generating an output audio signal as

25 claimed in claim 5, the apparatus delivering; and

_____signal output means for receiving the output audio
signal to signal output means from said apparatus.

7. (Cancelled).

8. (Previously Presented) A data carrier storing a computer
program for execution by a processor, the computer program

describing ~~causing the processor to execute the~~ method as claimed
in claim 1.